

==== Cisco Router Baseconfiguration

```
Router(config)# hostname hostname

Router(config)# enable secret password

Router(config)# line console 0
Router(config-line)# password password
Router(config-line)# login

Router(config-line)# line vty 0 4
Router(config-line)# password password
Router(config-line)# login
Router(config-line)# transport input {ssh | telnet | none | all}

Router(config-line)# exit
Router(config)# service password-encryption

Router(config)# banner motd delimiter message delimiter

Router(config)# copy running-config startup-config

<code>
```

```
Router> enable Router# configure terminal Enter configuration commands, one per line. End with
CNTL/Z. Router(config)# hostname R1 R1(config)# R1(config)# enable secret class R1(config)#
R1(config)# line console 0 R1(config-line)# password cisco R1(config-line)# login R1(config-line)#
exit R1(config)# R1(config)# line vty 0 4 R1(config-line)# password cisco R1(config-line)# login
R1(config-line)# transport input ssh telnet R1(config-line)# exit R1(config)# R1(config)# service
password-encryption R1(config)# R1(config)# banner motd # Enter TEXT message. End with the
character '#'. * WARNING: Unauthorized access is prohibited! * R1(config)# R1# copy running-
config startup-config Destination filename [startup-config]? Building configuration... [OK] R1#
</code>
```

From:

<https://wiki.djal.in/> - IT - wiki

Permanent link:

<https://wiki.djal.in/doku.php/howto/cisco/router/baseconfiguration?rev=1727260167>

Last update: 2024/09/25 10:29

