====== Cisco Router Baseconfiguration

```
Router(config)# hostname hostname

Router(config)# enable secret password

Router(config)# line console 0
Router(config-line)# password password
Router(config-line)# login

Router(config-line)# line vty 0 4
Router(config-line)# password password
Router(config-line)# login
Router(config-line)# transport input {ssh | telnet | none | all}

Router(config-line)# exit
Router(config)# service password-encryption

Router(config)# banner motd delimiter message delimiter

Router(config)# copy running-config startup-config


<code>
```

Router> enable Router# configure terminal Enter configuration commands, one per line. End with CNTL/Z. Router(config)# hostname R1 R1(config)# R1(config)# enable secret class R1(config)# R1(config)# line console 0 R1(config-line)# password cisco R1(config-line)# login R1(config-line)# exit R1(config)# R1(config)# line vty 0 4 R1(config-line)# password cisco R1(config-line)# login R1(config-line)# transport input ssh telnet R1(config-line)# exit R1(config)# R1(config)# service password-encryption R1(config)# R1(config)# banner motd # Enter TEXT message. End with the character '#'. ********** WARNING: Unauthorized access is prohibited! ********** R1(config)# R1# copy running-config startup-config Destination filename [startup-config]? Building configuration... [OK] R1# </code>

From:
https://wiki.djal.in/ - **IT - wiki**

Permanent link:
https://wiki.djal.in/doku.php/howto/cisco/router/baseconfiguration?rev=1727260167

Last update: **2024/09/25 10:29**